

**Specification/standard**
**规范 / 标准**

Specification	IEC 61984
规范	IEC 60664-1
	IEC 61373
Authentication	
认证	

**Insert 插芯**

接插件针数	3+PE
Number of contacts	
依据 IEC61984 的额定电压	
Rated voltage according to IEC61984	
额定电流	10A
Rated current	
相对地额定电压	230V
Rated voltage conductor-ground	
相间额定电压	400V
Rated voltage conductor-conductor	
额定脉冲电压	4kV
Rated impulse voltage	
污染程度	3
Pollution degree	
绝缘电阻	$\geq 10^{10}\Omega$
Insulation resistance	
材料	阻燃 PC
Material	Flame retardant PC
工作温度范围	-40°C ~ +125°C
Limiting temperatures	
阻燃等级	EN45545-2:R22/R23 UL94-V0
Flame retardant grade	
机械寿命	$\geq 500$ 次
Mechanical life	


**Contacts 插针**

材料	铜合金
Material	Copper alloy
表面处理	镀银
Surface treatment	Silver plated
接触电阻	$\leq 2.5m\Omega$
Contact resistance	
PE 螺钉连接	
PE screw connection	
mm <sup>2</sup>	1-2.5mm <sup>2</sup>
AWG	18-14

**Current carrying capacity**
**电流承载能力**

连接器的电流承载能力受接触件和绝缘部件的热负荷能力限制。降额曲线在不超过允许的最高温度下，有限显示电流均匀持续地通过连接器的每个接点。测试方法参照 DIN EN 60512-5。

The current carrying capacity of the connector is limited by the thermal load capacity of the contact and insulating parts. Under the condition that the derating curve does not exceed the maximum allowable temperature, the limited display current uniformly and continuously passes through each contact of the connector. The test method refers to DIN EN 60512-5.


**环境温度 (°C)**

- ① 导体截面积: 2.5mm<sup>2</sup>
- ② 导体截面积: 1.5mm<sup>2</sup>
- ③ 导体截面积: 1.0mm<sup>2</sup>

**Ambient temperature (°C)**





- ① conductor cross section : 2.5mm<sup>2</sup>
- ② conductor cross section : 1.5mm<sup>2</sup>
- ③ conductor cross section : 1.0mm<sup>2</sup>









针数量 Number of contacts

3 +

Shell size: matching 3A/3B shell

外壳尺寸: 匹配 3A/3B 外壳

Description 描述	Specification 型号	Order number 订货号		Scale drawings 比例图	Dimension unit 尺寸单位 (mm)
		公插芯 Male	母插芯 Female		
螺栓连接 Screw terminal  	HDC-HQ3-M	113060100497			
	HDC-HQ3-F		113060200483		

Number	Series	Scope of application	Specification	Order number	Place of production
序号	系列	适用范围	型号	订货号	产地
1	HDC-HD 系列退针器 HDC-HD series contacts retractor 	10A 公针 10A male contacts	HDC-HD-CX	113030400143	四川 - 绵阳 Sichuan-mianyang
		10A 母针 10A female contacts	HDC-HD-CX	113030400143	四川 - 绵阳 Sichuan-mianyang
2	HDC-HE 系列退针器 HDC-HE series contacts retractor   	16A 公针 16A male contacts	HDC-HE-CX	113030400142	四川 - 绵阳 Sichuan-mianyang
		16A 母针 16A female contacts	HDC-HE-CX	113030400142	四川 - 绵阳 Sichuan-mianyang
		16A 公针 16A male contacts	HDC-HE-CX/P	113030400146	四川 - 绵阳 Sichuan-mianyang
		16A 母针 16A female contacts	HDC-HE-CX/P	113030400146	四川 - 绵阳 Sichuan-mianyang
3	HDC-HMC 系列退针器 HDC-HMC series contacts retractor   	40A 公针 40A male contacts	HDC-HC-CX	113030400144	四川 - 绵阳 Sichuan-mianyang
		40A 母针 40A female contacts	HDC-HC-CX	113030400144	四川 - 绵阳 Sichuan-mianyang
		40A 公针 40A male contacts	HDC-HC-CX/P	113030400148	四川 - 绵阳 Sichuan-mianyang
		40A 母针 40A female contactsc	HDC-HC-CX/P	113030400148	四川 - 绵阳 Sichuan-mianyang
4	HDC-HDsub 系列退针器 HDC-HDsub series contacts retractor 	5A 公针 5A male contacts	HDC-DSUB9-CX	113030400145	四川 - 绵阳 Sichuan-mianyang
		5A 母针 5A female contacts	HDC-DSUB9-CX	113030400145	四川 - 绵阳 Sichuan-mianyang
5	HDC-HM200 系列退针器 HDC-HM200 series contacts retractor 	200A 公针 200A male contacts	HDC-HM200-CX	112980003652	四川 - 绵阳 Sichuan-mianyang
		200A 母针 200A female contacts	HDC-HM200-CX	112980003652	四川 - 绵阳 Sichuan-mianyang
6	HDC-HM2C100 系列退针器 HDC-HM2C100 series contacts retractor 	100A 公针 100A male contacts	HDC-HM2C100-CX	112980003651	四川 - 绵阳 Sichuan-mianyang
		100A 母针 100A female contacts	HDC-HM2C100-CX	112980003651	四川 - 绵阳 Sichuan-mianyang

外壳 / V 系列

外壳 / D 系列

连接体 / C 系列

连接体 / M 系列

连接体 / W 系列

连接体 / O 系列

连接体 / 混装系列

连接体 / C 系列

重载附件

Number	Series	Crimping wire diameter	Specification	Order number	
序号	系列	压接线径	型号	订货号	
1	5A/10A 	0.34-4mm <sup>2</sup>	M22520/1-01(DMC)	531030600020	
2	16A/40A 	0.34-10mm <sup>2</sup>	KNIPEX 四心轴压线钳 (97 52 65) KNIPEX Four spindleCrimping pliers (97 52 65)	531030600052	
3	70A/350A 	6-120mm <sup>2</sup>	EK60/22L	531030600010	
		配套压接工装 Matching crimping tooling			
		编码 Code	名称 Name	备注 remarks	
		531030600074	EK60/22 六方带点压模 6mm <sup>2</sup> EK60/22 Hexagonal point pressing die 6mm <sup>2</sup>		
		531030600075	EK60/22 六方带点压模 10mm <sup>2</sup> EK60/22 Hexagonal point pressing die 10mm <sup>2</sup>		
		531030600076	EK60/22 六方带点压模 16mm <sup>2</sup> EK60/22 Hexagonal point pressing die 16mm <sup>2</sup>		
		531030600077	EK60/22 六方带点压模 25mm <sup>2</sup> EK60/22 Hexagonal point pressing die 25mm <sup>2</sup>		
		531030600078	EK60/22 六方带点压模 35mm <sup>2</sup> EK60/22 Hexagonal point pressing die 35mm <sup>2</sup>		
		531030600079	EK60/22 六方带点压模 50mm <sup>2</sup> EK60/22 Hexagonal point pressing die 50mm <sup>2</sup>		
		531030600066	EK60/22 六方带点压模 70mm <sup>2</sup> EK60/22 Hexagonal point pressing die 70mm <sup>2</sup>		
531030600067	EK60/22 六方带点压模 95mm <sup>2</sup> EK60/22 Hexagonal point pressing die 95mm <sup>2</sup>				
531030600068	EK60/22 六方带点压模 120mm <sup>2</sup> EK60/22 Hexagonal point pressing die 120mm <sup>2</sup>				
4	650A 	150-240mm <sup>2</sup>	EK120/42L		
		配套压接工装 Matching crimping tooling			
		编码 Code	名称 Name	备注 remarks	
		531030600069	EK120/42 六方带点压模 150mm <sup>2</sup> EK120/42 Hexagonal point pressing die 150mm <sup>2</sup>		
		531030600070	EK120/42 六方带点压模 185mm <sup>2</sup> EK120/42 Hexagonal point pressing die 185mm <sup>2</sup>		
531030600071	EK120/42 六方带点压模 240mm <sup>2</sup> EK120/42 Hexagonal point pressing die 240mm <sup>2</sup>				